NSN 5950-01-333-4921

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-333-4921

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 1.300 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.725 inches single mounting facility single center group |
| Overall Height: |
| 1.225 inches |
| Overall Width: |
| 1.000 inches |
| Mounting Hole Diameter: |
| 0.140 inches single group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 3.60 microhenries single component single winding |
| Frequency Rating: |
| 10.0 kilohertz single component |
| Maximum Operating Temp: |
| 130.0 degrees celsius |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Operating Current: |
| 16.0 amperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 0.015 single component single winding |
| Precious Material And Location: |
| Terminals gold |
| Precious Material: |
| Gold |
| Test Data Document: |

33604-2-18556 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

NSN 5950-01-333-4921

Reactor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A058b0