

View Online at <https://aerobasegroup.com/nsn/5950-01-333-4926>

Reliability Indicator:

Not established

Overall Length:

1.300 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.700 inches single mounting facility single center group

Overall Height:

1.225 inches

Overall Width:

1.000 inches

Mounting Hole Diameter:

0.140 inches single group

Frequency Rating:

125.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

7.7 amperes ac single component single secondary

Winding Power Rating:

91.4 volts-amperes single component single secondary

Winding Operating Voltage:

39.59 ac volts single component single primary

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Test Data Document:

33604-2-18557 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

5 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0