## NSN 5950-01-333-8933

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-333-8933
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant and humidity resistant
Overall Length:
1.000 inches
Turn Quantity:
168 single component single winding
Overall Height:
0.500 inches
Overall Width:
1.240 inches
Inductance Type:
Fixed
Inductance Rating:
300.00 microhenries single component single winding
Frequency Rating:
15.75 kilohertz single component
Maximum Operating Temp:
170.0 degrees celsius
Distance Between Mounting Facility Centers:
0.625 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Method:
Terminal single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Winding Conductor Size:
0.02257 inches american wire gage single component single winding
Winding Operating Current:
2.5 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.300 single component single winding
Test Data Document:
88818-a504a494 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
2 turret

N/a

Shelf Life:

## NSN 5950-01-333-8933

Reactor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A058b0