

View Online at <https://aerobasegroup.com/nsn/5950-01-333-8937>

**Reliability Indicator:**

Not established

**Overall Length:**

1.415 inches

**Mounting Hole Diameter:**

0.150 inches single group

**Frequency Rating:**

19.0 kilohertz single component and 30.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Outside Diameter:**

2.390 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

3 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component and 1 tertiary single component

**Features Provided:**

W/rectifier

**Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:**

1.920 inches single mounting facility single center group

**Winding Operating Current:**

1.0 amperes dc single component single primary

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

2.230 inches single mounting facility single center group

**Winding Operating Voltage:**

15.00 dc volts single component single primary

**Precious Material And Location:**

Terminals gold and terminals silver

**Precious Material:**

Gold and silver

**Test Data Document:**

07187-4017991 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

3 pin and 5 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0