

View Online at <https://aerobasegroup.com/nsn/5950-01-333-8937>

Reliability Indicator:

Not established

Overall Length:

1.415 inches

Mounting Hole Diameter:

0.150 inches single group

Frequency Rating:

19.0 kilohertz single component and 30.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Outside Diameter:

2.390 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

3 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component and 1 tertiary single component

Features Provided:

W/rectifier

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

1.920 inches single mounting facility single center group

Winding Operating Current:

1.0 amperes dc single component single primary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

2.230 inches single mounting facility single center group

Winding Operating Voltage:

15.00 dc volts single component single primary

Precious Material And Location:

Terminals gold and terminals silver

Precious Material:

Gold and silver

Test Data Document:

07187-4017991 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 pin and 5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0