## NSN 5950-01-334-3755

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-334-3755

**Reliability Indicator:** Not established **Overall Length:** 4.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.600 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.600 inches single mounting facility single center group **Overall Width:** 4.000 inches Frequency Rating: 45.0 hertz single component and 440.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component **Body Height: 3.700** inches **Maximum Operating Temp:** 130.0 degrees celsius **Inclosure Type:** Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded hole single group **Winding Function And Quantity:** 1 primary single component and 2 secondary single component **Thread Size:** 0.164 inches single group **Winding Operating Current:** 23.0 milliamperes ac single component 2nd secondary **Winding Power Rating:** 84.82 volts-amperes single component 1st secondary Winding Operating Voltage: 29.25 ac volts single component 1st secondary **Test Data Document:** 07187-8502991 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 7 threaded stud

N/a

Shelf Life:

## NSN 5950-01-334-3755

Power Transformer - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A058b0