NSN 5950-01-334-6715

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-334-6715

Rε	lia	bili	ty	Ind	icate	or:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and fungus resistant and vibration resistant and flame resistant

Overall Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.950 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility single center group

Overall Height:

1.500 inches

Overall Width:

0.800 inches

Inductance Type:

Fixed

Inductance Rating:

780.00 microhenries single component single winding

Frequency Rating:

800.0 hertz single component

Maximum Operating Temp:

130.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding

Thread Size:

0.112 inches single group

Winding Operating Current:

1.9 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.250 single component single winding

Test Data Document:

17863-7137148 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

NSN 5950-01-334-6715

Reactor - Page 2 of 2



Terminal Type And Quantity:				
2 turret				
Shelf Life:				
N/a				
Unit Of Measure:				
Demilitarization:				
No				

Fiig: A058b0