

View Online at <https://aerobasegroup.com/nsn/5950-01-334-8632>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and vibration resistant

Overall Length:

2.810 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.210 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.520 inches single mounting facility single center group

Overall Height:

2.430 inches

Overall Width:

2.420 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

5.36 amperes ac single component all secondary

Winding Power Rating:

150.0 volts-amperes single component all secondary

Winding Operating Voltage:

28.00 ac volts single component all secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

Specification Data:

81349-mil-t-27/337 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0