

View Online at <https://aerobasegroup.com/nsn/5950-01-334-9753>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Salt water resistant and vibration resistant

Overall Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.400 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Overall Height:

2.150 inches

Overall Width:

3.700 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

1.5 amperes dc single component single secondary

Winding Operating Voltage:

29.70 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

7 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0