

View Online at <https://aerobasegroup.com/nsn/5950-01-336-0229>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Salt spray resistant and vibration resistant

Overall Length:

2.100 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.700 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.600 inches single mounting facility single center group

Overall Height:

1.870 inches

Overall Width:

2.000 inches

Frequency Rating:

33.0 kilohertz single component

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

10.0 amperes ac single component 1st secondary

Dc Resistance Rating In Ohms:

30.000 single component single primary

Winding Operating Voltage:

36.27 ac volts single component 1st secondary

Test Data Document:

13973-841327 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0