

View Online at <https://aerobasegroup.com/nsn/5950-01-336-0231>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

2.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.600 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Overall Height:

1.640 inches

Overall Width:

1.650 inches

Inductance Type:

Fixed

Inductance Rating:

6.50 millihenries single component single winding

Frequency Rating:

270.0 hertz single component

Maximum Operating Temp:

90.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding

Thread Size:

0.138 inches single group

Winding Operating Current:

2.5 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.320 single component single winding

Test Data Document:

13973-841328 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0