## NSN 5950-01-336-0232

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-336-0232

**Reliability Indicator:** 

Not established

**Hazardous Locations/environmental Protection:** 

Moisture resistant and vibration resistant

**Overall Length:** 

3.750 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

3.320 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

1.820 inches single mounting facility single center group

**Overall Height:** 

2.250 inches

**Inductance Type:** 

Fixed

**Inductance Rating:** 

440.00 microhenries single component single winding

**Frequency Rating:** 

270.0 hertz single component

**Body Width:** 

2.250 inches

**Maximum Operating Temp:** 

90.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

**Mounting Facility Quantity:** 

4 single group

**Mounting Method:** 

Threaded hole single group

Rating Method:

Electrical single component single winding

Thread Size:

0.164 inches single group

**Winding Conductor Size:** 

0.14430 inches american wire gage single component single winding

**Winding Operating Current:** 

25.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.007 single component single winding

**Test Data Document:** 

13973-841329 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **NSN 5950-01-336-0232** Reactor - Page 2 of 2



Thread Series Designator:
Unc single group
Terminal Type And Quantity:
2 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A058b0