## NSN 5950-01-336-0232

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-336-0232

Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Moisture resistant and vibration resistant
Overall Length:
3.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.320 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.820 inches single mounting facility single center group
Overall Height:
2.250 inches
Inductance Type:
Fixed
Inductance Rating:
440.00 microhenries single component single winding
Frequency Rating:
270.0 hertz single component
Body Width:
2.250 inches
Maximum Operating Temp:
90.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Rating Method:
Electrical single component single winding
Thread Size:
0.164 inches single group
Winding Conductor Size:
0.14430 inches american wire gage single component single winding
Winding Operating Current:
25.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.007 single component single winding
Test Data Document:

13973-841329 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# NSN 5950-01-336-0232

Reactor - Page 2 of 2



Unc single group

#### Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A058b0

