

View Online at <https://aerobasegroup.com/nsn/5950-01-336-1783>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and fungus resistant and flame resistant and vibration resistant

Overall Length:

0.350 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.200 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.200 inches single mounting facility single center group

Overall Width:

0.350 inches

Frequency Rating:

125.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Height:

0.280 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.41 amperes ac single component single primary

Winding Operating Voltage:

4.24 ac millivolts single component single secondary

Test Data Document:

33604-2-18551 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0