NSN 5950-01-336-9987

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-336-9987

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.656 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.900 inches single mounting facility single center group |
| Frequency Rating: |
| 27.8 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.040 inches |
| Body Width: |
| 1.280 inches |
| Body Height: |
| 1.280 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 6.2 amperes ac single component 2nd secondary |
| Winding Operating Voltage: |
| 150.00 ac volts single component single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |