

View Online at <https://aerobasegroup.com/nsn/5950-01-337-5546>

Reliability Indicator:

Not established

Overall Length:

2.700 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.060 inches single mounting facility single center group and 2.120 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches single mounting facility single center group

Overall Height:

1.360 inches

Overall Width:

1.710 inches

Mounting Slot Width:

0.170 inches single group

Frequency Rating:

50.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

30.0 amperes ac single component single secondary

Winding Power Rating:

270.0 volts-amperes single component single secondary

Winding Operating Voltage:

9.00 ac volts single component single secondary

Test Data Document:

19623-007439 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0