
# NSN 5950-01-337-6418

Reactor - Page 1 of 1





### **Reliability Indicator:**

Not established

#### **Overall Length:**

1.660 inches

# Inductance Rating:

6.10 microhenries single component all winding

#### **Frequency Rating:**

100.0 kilohertz single component

#### **Overall Diameter:**

Between 1.372 inches and 1.378 inches

### Maximum Operating Temp:

130.0 degrees celsius

#### Winding Quantity:

2 single component

### Inclosure Type:

Fully enclosed

# **Mounting Facility Quantity:**

1 single group

# **Mounting Method:**

Threaded hole single group

## **Rating Method:**

Electrical single component all winding

### Thread Size:

0.138 inches single group

### Winding Operating Current:

30.0 amperes dc single component all winding

### Dc Resistance Rating In Ohms:

0.002 single component all winding

### **Test Data Document:**

19623-007433 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Thread Series Designator:

Unc single group

#### **Terminal Type And Quantity:**

4 tab, solder lug

#### Shelf Life:

N/a

# Unit Of Measure:

---

### Demilitarization:

No

# Fiig:

A058b0