

View Online at <https://aerobasegroup.com/nsn/5950-01-337-6424>

**Reliability Indicator:**

Not established

**Overall Length:**

2.140 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.583 inches single mounting facility single center group and 1.603 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.190 inches single mounting facility single center group and 1.210 inches single mounting facility single center group

**Overall Height:**

1.250 inches

**Overall Width:**

1.560 inches

**Mounting Hole Diameter:**

0.171 inches single group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

2.59 amperes ac single component single secondary

**Winding Power Rating:**

82.3 volts-amperes single component single secondary

**Winding Operating Voltage:**

31.80 ac volts single component single secondary

**Special Features:**

Secondary winding terminals are split for dual connection

**Test Data Document:**

19623-007321 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0