

View Online at <https://aerobasegroup.com/nsn/5950-01-337-6424>

Reliability Indicator:

Not established

Overall Length:

2.140 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.583 inches single mounting facility single center group and 1.603 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.190 inches single mounting facility single center group and 1.210 inches single mounting facility single center group

Overall Height:

1.250 inches

Overall Width:

1.560 inches

Mounting Hole Diameter:

0.171 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.59 amperes ac single component single secondary

Winding Power Rating:

82.3 volts-amperes single component single secondary

Winding Operating Voltage:

31.80 ac volts single component single secondary

Special Features:

Secondary winding terminals are split for dual connection

Test Data Document:

19623-007321 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0