

View Online at <https://aerobasegroup.com/nsn/5950-01-337-6425>

Reliability Indicator:

Not established

Overall Length:

2.140 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.593 inches 1st mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.380 inches 2nd mounting facility single center group and 1.400 inches 2nd mounting facility single center group

Overall Height:

1.410 inches

Overall Width:

1.750 inches

Mounting Hole Diameter:

0.171 inches 2nd group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Unthreaded hole 2nd group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches 1st group

Winding Operating Current:

13.9 amperes ac single component single secondary

Winding Power Rating:

111.2 volts-amperes single component single secondary

Winding Operating Voltage:

8.00 ac volts single component single secondary

Special Features:

Secondary winding terminals are split for dual connection

Test Data Document:

19623-007729 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc 1st group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0