

View Online at <https://aerobasegroup.com/nsn/5950-01-339-5097>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Humidity resistant

**Overall Length:**

3.880 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.180 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.750 inches single mounting facility single center group

**Overall Height:**

3.250 inches

**Overall Width:**

3.350 inches

**Mounting Slot Width:**

0.257 inches single group

**Frequency Rating:**

47.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Primary and secondary shielded and brought out to terminal single component

**Maximum Operating Temp:**

60.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Winding Operating Current:**

7.0 amperes dc single component 3rd secondary

**Winding Power Rating:**

30.0 volts-amperes single component 1st secondary

**Winding Operating Voltage:**

35.00 ac volts single component 4th secondary

**Special Features:**

One primary winding; 5 secondary windings

**Terminal Type And Quantity:**

15 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0