

View Online at <https://aerobasegroup.com/nsn/5950-01-339-5097>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Humidity resistant

Overall Length:

3.880 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.180 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Overall Height:

3.250 inches

Overall Width:

3.350 inches

Mounting Slot Width:

0.257 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal single component

Maximum Operating Temp:

60.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Winding Operating Current:

7.0 amperes dc single component 3rd secondary

Winding Power Rating:

30.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

35.00 ac volts single component 4th secondary

Special Features:

One primary winding; 5 secondary windings

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0