

View Online at <https://aerobasegroup.com/nsn/5950-01-339-6683>

Reliability Indicator:

Not established

Turn Quantity:

16 single component 1st winding 24 single component 2nd winding

Mounting Hole Diameter:

0.088 inches single group

Inductance Rating:

15.00 microhenries single component 1st winding 32.00 microhenries single component 2nd winding

Frequency Rating:

10.0 kilohertz single component

Core Construction:

Solid single component

Body Length:

Between 0.410 inches and 0.420 inches

Overall Diameter:

0.793 inches

Maximum Operating Temp:

130.0 degrees celsius

Winding Quantity:

2 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component all winding and winding turns single component all winding

Winding Conductor Size:

0.03196 inches american wire gage single component 1st winding 0.02010 inches american wire gage single component 2nd winding

Winding Operating Current:

6.0 amperes dc single component 1st winding 1.5 amperes dc single component 2nd winding

Dc Resistance Rating In Ohms:

0.010 single component 1st winding 0.036 single component 2nd winding

Winding Operating Voltage:

50.00 ac pounds per hour wet single component all winding

Test Data Document:

45413-142608 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0