

View Online at <https://aerobasegroup.com/nsn/5950-01-339-6684>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

3.040 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.120 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Overall Height:

2.620 inches

Overall Width:

2.620 inches

Mounting Slot Width:

0.190 inches single group

Inductance Rating:

30.00 millihenries single component single winding

Frequency Rating:

360.0 hertz single component

Core Construction:

Solid single component

Maximum Operating Temp:

130.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Rating Method:

Electrical single component single winding

Winding Operating Current:

3.0 amperes dc single component single winding

Dc Resistance Rating In Ohms:

1.150 single component single winding

Winding Operating Voltage:

26.40 ac volts single component single winding

Test Data Document:

97942-157c157 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0