

View Online at <https://aerobasegroup.com/nsn/5950-01-339-8204>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

6.030 inches

Overall Height:

3.570 inches

Mounting Hole Diameter:

0.500 inches 2nd group

Mounting Slot Width:

0.187 inches 1st group

Frequency Rating:

10.0 kilohertz all components

Input-output Phase Relationship:

Single phase to single phase all components

Winding Shielding Method:

Internal shield brought out to terminal 2nd component

Body Width:

3.440 inches

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

5.375 inches 3rd mounting facility single center group

Mounting Tab Width:

0.625 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 2nd group

Mounting Method:

Unthreaded hole 2nd group

Rating Method:

Electrical all components single primary

Winding Function And Quantity:

1 primary 3rd component and 3 secondary 3rd component

Features Provided:

W/rectifier

Winding Operating Current:

30.0 milliamperes ac 1st component 4th secondary

Dc Resistance Rating In Ohms:

2.750 1st component 4th secondary

Winding Power Rating:

7.47 volts-amperes 3rd component 3rd secondary

Winding Operating Voltage:

6.01 ac volts 2nd component 4th secondary

Terminal Type And Quantity:

36 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0