NSN 5950-01-339-8204

Transformer Assembly - Page 1 of 2



| Transformer Assembly Tage 1 of 2 | |
|---|--|
| View Online at https://aerobasegroup.com/nsn/5950-01-339-8204 | |
| Reliability Indicator: | |
| Not established | |
| Hazardous Locations/environmental Protection: | |
| Vibration resistant | |
| Overall Length: | |
| 6.030 inches | |
| Overall Height: | |
| 3.570 inches | |
| Mounting Hole Diameter: | |
| 0.500 inches 2nd group | |
| Mounting Slot Width: | |
| 0.187 inches 1st group | |
| Frequency Rating: | |
| 10.0 kilohertz all components | |
| Input-output Phase Relationship: | |
| Single phase to single phase all components | |
| Winding Shielding Method: | |
| Internal shield brought out to terminal 2nd component | |
| Body Width: | |
| 3.440 inches | |
| Maximum Operating Temp: | |
| 130.0 degrees celsius | |
| Distance Between Mounting Facility Centers: | |
| 5.375 inches 3rd mounting facility single center group | |

Mounting Tab Width:

0.625 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 2nd group

Mounting Method:

Unthreaded hole 2nd group

Rating Method:

Electrical all components single primary

Winding Function And Quantity:

1 primary 3rd component and 3 secondary 3rd component

Features Provided:

W/rectifier

Winding Operating Current:

30.0 milliamperes ac 1st component 4th secondary

Dc Resistance Rating In Ohms:

2.750 1st component 4th secondary

NSN 5950-01-339-8204

Transformer Assembly - Page 2 of 2



Winding Power Rating:

7.47 volts-amperes 3rd component 3rd secondary

Winding Operating Voltage:

6.01 ac volts 2nd component 4th secondary

Terminal Type And Quantity:

36 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A058b0