

View Online at <https://aerobasegroup.com/nsn/5950-01-340-1295>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and flame resistant and vibration resistant

Overall Length:

2.210 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.620 inches single mounting facility single center group and 1.630 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.932 inches single mounting facility single center group and 0.942 inches single mounting facility single center group

Overall Height:

1.750 inches

Overall Width:

1.870 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

20.0 amperes ac single component single secondary

Winding Power Rating:

102.0 volts-amperes single component single secondary

Winding Operating Voltage:

5.10 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0