

View Online at <https://aerobasegroup.com/nsn/5950-01-340-1296>

Reliability Indicator:

Not established

Overall Length:

4.452 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.740 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.228 inches single mounting facility single center group

Mounting Slot Width:

0.236 inches single group

Frequency Rating:

48.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to terminal single component

Body Width:

3.861 inches

Body Height:

4.137 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Winding Operating Current:

500.0 milliamperes ac single component 3rd secondary

Winding Power Rating:

40.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

31.20 ac volts single component 3rd secondary

Special Features:

A no. 22 awg wire lead is connected to the black/red wire lead of the second primary winding

Terminal Type And Quantity:

17 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0