Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-340-8676

| Reliability Indicator: |
|--|
| Not established |
| Overall Length: |
| Between 1.220 inches and 1.280 inches |
| Turn Quantity: |
| 16 single component 1st secondary |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.900 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.800 inches single mounting facility single center group |
| Overall Width: |
| Between 0.980 inches and 1.020 inches |
| Inductance Rating: |
| 215.00 microhenries single component single primary |
| Frequency Rating: |
| 100.0 kilohertz single component |
| Coil Form Type: |
| Solid single component |
| Body Height: |
| 1.000 inches |
| Maximum Operating Temp: |
| 155.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded hole single group |
| Rating Method: |
| Winding turns single component all secondary |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Winding Conductor Size: |
| 0.02010 inches american wire gage single component 1st secondary |
| Test Data Document: |
| 13160-7573710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 9 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Radio Frequency Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

