

View Online at <https://aerobasegroup.com/nsn/5950-01-341-7366>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Moisture resistant and vibration resistant

**Overall Length:**

2.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.688 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.423 inches single mounting facility single center group and 1.453 inches single mounting facility single center group

**Overall Width:**

2.062 inches

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Height:**

2.500 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

3.0 amperes ac single component single secondary

**Winding Power Rating:**

15.0 volts-amperes single component single secondary

**Winding Operating Voltage:**

5.00 ac volts single component single secondary

**Test Data Document:**

13499-672-0636 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0