## NSN 5950-01-342-2782

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-342-2782

view Offilite at https://aerobasegroup.com/nsn/0550-01-542-2762
Reliability Indicator:
Not established
Overall Length:
0.450 inches
Turn Quantity:
12 single component all winding
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.350 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.300 inches single mounting facility single center group
Overall Width:
0.410 inches
Inductance Type:
Fixed
Inductance Rating:
100.00 microhenries single component all winding
Frequency Rating:
1.0 kilohertz single component
Body Height:
0.305 inches
Maximum Operating Temp:
155.0 degrees celsius
Winding Quantity:
3 single component
Inclosure Type:
Fully enclosed
Mounting Method:
Terminal single group
Rating Method:
Electrical single component all winding and winding turns single component all winding
Features Provided:
Tinned wire leads
Winding Conductor Size:
0.01003 inches american wire gage single component all winding
Winding Operating Current:
125.0 milliamperes ac single component all winding
Dc Resistance Rating In Ohms:
0.060 single component all winding
Test Data Document:
95105-276-0063 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

6 pin

**Terminal Type And Quantity:** 

## NSN 5950-01-342-2782

Reactor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0