

View Online at <https://aerobasegroup.com/nsn/5950-01-342-3404>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant and vibration resistant

Mounting Hole Diameter:

0.217 inches single group

Frequency Rating:

20.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

0.750 inches

Body Outside Diameter:

1.210 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Terminal single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Features Provided:

Tinned wire leads and color coded terminal

Winding Operating Voltage:

4.00 ac pounds per hour wet single component 1st secondary 8.60 ac pounds per hour dry single component 2nd secondary and 9.00 ac pounds per hour with retaining chain single component 2nd secondary 11.80 ac pounds per hour dry single component 3rd secondary and 12.20 ac pounds per hour with retaining chain single component 3rd secondary 22.20 ac pounds per hour dry single component 4th secondary and 22.60 ac pounds per hour with retaining chain single component 4th secondary 4.00 ac pounds per hour wet single component single primary

Special Features:

One primary winding; five secondary windings

Test Data Document:

13499-672-0652 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

13 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No