

View Online at <https://aerobasegroup.com/nsn/5950-01-343-0851>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

3.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Overall Height:

3.375 inches

Overall Width:

2.812 inches

Mounting Slot Width:

0.169 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

3.0 amperes ac single component 2nd secondary

Winding Power Rating:

57.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

38.00 ac volts single component 3rd secondary

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0