

View Online at <https://aerobasegroup.com/nsn/5950-01-343-8398>

Reliability Indicator:

Not established

Overall Length:

0.499 inches

Impedance Rating In Ohms:

8000.0 single component single secondary and 10000.0 single component single secondary

Frequency Rating:

300.0 hertz single component and 100.0 kilohertz single component

Maximum Transformer Power Rating:

100.0 milliwatts single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Overall Diameter:

0.344 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Color coded lead and tinned wire leads

Winding Operating Current:

2.0 milliamperes dc single component single primary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

7 wire lead

Specification Data:

81349-mil-t-27/172 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0