## NSN 5050-01-3/3-8860



| Power Transformer - Page 1 of 2   | AG |
|---|----|
| View Online at https://aerobasegroup.com/nsn/5950-01-343-8869             |    |
| Reliability Indicator:  |    |
| Not established   |    |
| Overall Length:   |    |
| 7.500 inches  |    |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |    |
| 5.625 inches single mounting facility single center group                 |    |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |    |
| 3.625 inches single mounting facility single center group                 |    |
| Overall Height:   |    |
| 6.500 inches  |    |
| Overall Width:  |    |
| 6.875 inches  |    |
| Mounting Slot Width:  |    |
| 0.312 inches single group   |    |
| Frequency Rating:   |    |
| 60.0 hertz single component   |    |
| Input-output Phase Relationship:  |    |
| Single phase to single phase single component                             |    |
| Maximum Transformer Power Rating  |    |

#### Maximum Transformer Power Rating:

1.5 kilovolt-ampere single component

### **Maximum Operating Temp:**

105.0 degrees celsius

#### **End Application:**

Usns henry j kaiser class tao

#### Inclosure Type:

Open

## **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Slot single group

#### Winding Function And Quantity:

2 primary single component and 2 secondary single component

#### **Winding Operating Current:**

12.5 amperes ac single component all secondary

## **Criticality Code Justification:**

Feat

## **Winding Operating Voltage:**

240.00 ac volts single component all primary

#### **Special Features:**

Weapon system essential

#### **Terminal Type And Quantity:**

8 tab, solder lug

# NSN 5950-01-343-8869

Power Transformer - Page 2 of 2



| _ |   |   |     | - |      |  |
|---|---|---|-----|---|------|--|
| C | h | 0 | Iŧ. |   | ife: |  |
|   |   |   |     |   |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0