

View Online at <https://aerobasegroup.com/nsn/5950-01-345-1042>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 0.992 inches and 1.052 inches

Turn Quantity:

16 single component single winding

Inductance Type:

Fixed

Inductance Rating:

0.03 millihenries single component single winding and 0.034 millihenries single component single winding

Body Outside Diameter:

Between 0.673 inches and 0.703 inches

Maximum Operating Temp:

130.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Rating Method:

Electrical single component single winding and winding turns single component single winding

Winding Conductor Size:

0.03196 inches american wire gage single component single winding

Winding Operating Current:

2.5 amperes dc single component single winding

Special Features:

Nuclear hardness critical items

Nuclear Hardness Critical Feature:

Hardened

Test Data Document:

26055-844-043-001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0