

View Online at <https://aerobasegroup.com/nsn/5950-01-345-1042>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

Between 0.992 inches and 1.052 inches

**Turn Quantity:**

16 single component single winding

**Inductance Type:**

Fixed

**Inductance Rating:**

0.03 millihenries single component single winding and 0.034 millihenries single component single winding

**Body Outside Diameter:**

Between 0.673 inches and 0.703 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Winding Quantity:**

1 single component

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Rating Method:**

Electrical single component single winding and winding turns single component single winding

**Winding Conductor Size:**

0.03196 inches american wire gage single component single winding

**Winding Operating Current:**

2.5 amperes dc single component single winding

**Special Features:**

Nuclear hardness critical items

**Nuclear Hardness Critical Feature:**

Hardened

**Test Data Document:**

26055-844-043-001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0