

View Online at <https://aerobasegroup.com/nsn/5950-01-345-5596>

Reliability Indicator:

Not established

Overall Length:

4.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Overall Height:

3.875 inches

Overall Width:

4.000 inches

Mounting Hole Diameter:

0.196 inches single group

Mounting Slot Width:

0.196 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group or unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 5 secondary single component

Winding Operating Current:

200.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

200.00 dc volts single component 2nd secondary

Special Features:

2 primary windings; 5 secondary windings

Terminal Type And Quantity:

27 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0