

View Online at <https://aerobasegroup.com/nsn/5950-01-346-1695>

Reliability Indicator:

Not established

Overall Length:

3.075 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.258 inches single mounting facility single center group and 2.318 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.700 inches single mounting facility single center group

Overall Height:

1.800 inches

Overall Width:

1.285 inches

Frequency Rating:

20.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component and internal shield grounded to core and brought out to terminal single component

End Application:

6625-01-279-3446, oscilloscope

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Current:

103.0 milliamperes dc single component 1st secondary 5.0 milliamperes dc single component 2nd secondary and 15.0 milliamperes dc single component 2nd secondary 1.0 milliamperes dc single component 3rd secondary 140.0 milliamperes dc single component single primary

Winding Operating Voltage:

6.30 ac pounds per hour wet single component 1st secondary 297.00 ac pounds per hour wet single component 2nd secondary 134.00 ac pounds per hour wet single component 3rd secondary and 268.00 ac pounds per hour wet single component 3rd secondary and 598.00 ac pounds per hour wet single component 3rd secondary 2007.00 ac pounds per hour wet single component 4th secondary 38.18 ac pounds per hour wet single component single primary

Terminal Type And Quantity:

14 wire lead

Shelf Life:

N/a

Unit Of Measure:

Fig:

A058b0