

View Online at <https://aerobasegroup.com/nsn/5950-01-346-9706>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

3.440 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.428 inches single mounting facility single center group and 2.448 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.985 inches single mounting facility single center group and 2.015 inches single mounting facility single center group

Overall Height:

1.550 inches

Overall Width:

Between 2.062 inches and 2.680 inches

Mounting Hole Diameter:

0.143 inches single group and 0.158 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta and wye-wye

Winding Shielding Method:

Internally shielded single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Cooling Method:

Self-cooled

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

55.0 milliamperes ac single component single primary

Winding Power Rating:

11.0 volts-amperes single component single primary

Winding Operating Voltage:

32.50 ac volts single component 2nd secondary and 33.50 ac volts single component 2nd secondary

Test Data Document:

99167-5907286 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

13 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0