

View Online at <https://aerobasegroup.com/nsn/5950-01-347-1847>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

0.630 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.400 inches single mounting facility single center group

Overall Width:

0.630 inches

Inductance Rating:

7.50 millihenries single component single primary

Impedance Rating In Ohms:

3000.0 single component single primary

Frequency Rating:

250.0 hertz single component and 3.0 kilohertz single component

Primary To Secondary Turn Ratio:

1.4 to 1 single component

Body Height:

0.275 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

60.0 milliamperes ac single component single primary

Dc Resistance Rating In Ohms:

1.500 single component single secondary

Winding Operating Voltage:

21.21 ac volts single component single primary

Test Data Document:

99187-5905468 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0