

View Online at <https://aerobasegroup.com/nsn/5950-01-347-1847>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

0.630 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.400 inches single mounting facility single center group

**Overall Width:**

0.630 inches

**Inductance Rating:**

7.50 millihenries single component single primary

**Impedance Rating In Ohms:**

3000.0 single component single primary

**Frequency Rating:**

250.0 hertz single component and 3.0 kilohertz single component

**Primary To Secondary Turn Ratio:**

1.4 to 1 single component

**Body Height:**

0.275 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

60.0 milliamperes ac single component single primary

**Dc Resistance Rating In Ohms:**

1.500 single component single secondary

**Winding Operating Voltage:**

21.21 ac volts single component single primary

**Test Data Document:**

99187-5905468 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

8 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0