## NSN 5950-01-347-1849

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-347-1849
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Vibration resistant
Turn Quantity:
12 single component all winding
Mounting Hole Diameter:
0.146 inches single group and 0.166 inches single group
Inductance Type:
Fixed
Inductance Rating:
100.00 microhenries single component all winding
Frequency Rating:
1.0 kilohertz single component
Body Length:
0.500 inches
Body Outside Diameter:
1.375 inches
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
2 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Unthreaded hole single group
Rating Method:
Electrical single component all winding and winding turns single component all winding
Winding Conductor Size:
0.03589 inches american wire gage single component all winding
Dc Resistance Rating In Ohms:
0.050 single component all winding
Test Data Document:
99167-5905482 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-347-1849

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0