

View Online at <https://aerobasegroup.com/nsn/5950-01-347-5451>

Reliability Indicator:

Not established

Overall Length:

1.770 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.450 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.450 inches single mounting facility single center group

Overall Width:

1.770 inches

Frequency Rating:

80.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

150.0 kilovolt-ampere single component

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal single component

Body Height:

2.300 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

800.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

44.00 ac volts single component 3rd secondary

Test Data Document:

08748-tf58-005 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 quick disconnect, male and 11 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0