

View Online at <https://aerobasegroup.com/nsn/5950-01-348-7902>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and fungus resistant and salt spray resistant and vibration resistant

Frequency Rating:

100.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

0.500 inches

Overall Diameter:

Between 0.740 inches and 0.760 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.112 inches single group

Winding Operating Current:

75.0 milliamperes dc single component single secondary

Winding Power Rating:

5.7 volts-amperes single component single primary

Winding Operating Voltage:

60.00 dc volts single component single secondary

Test Data Document:

64547-805936 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0