# NSN 5950-01-348-7902

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-348-7902

## Reliability Indicator:

Not established

#### Hazardous Locations/environmental Protection:

Moisture resistant and fungus resistant and salt spray resistant and vibration resistant

## Frequency Rating:

100.0 kilohertz single component

### Input-output Phase Relationship:

Single phase to single phase single component

#### Body Length:

0.500 inches

**Overall Diameter:** 

Between 0.740 inches and 0.760 inches

#### Maximum Operating Temp:

125.0 degrees celsius

## Inclosure Type:

Fully enclosed

### Mounting Facility Quantity:

1 single group

#### **Mounting Method:**

Threaded hole single group

#### Winding Function And Quantity:

1 primary single component and 1 secondary single component

### Thread Size:

0.112 inches single group

#### Winding Operating Current:

75.0 milliamperes dc single component single secondary

#### Winding Power Rating:

5.7 volts-amperes single component single primary

#### Winding Operating Voltage:

60.00 dc volts single component single secondary

#### Test Data Document:

64547-805936 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Thread Series Designator:

Unc single group

#### Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5950-01-348-7902

Power Transformer - Page 2 of 2

**Fiig:** A058b0

