NSN 5950-01-348-7902

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-348-7902
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Moisture resistant and fungus resistant and salt spray resistant and vibration resistant
Frequency Rating:
100.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
0.500 inches
Overall Diameter:
Between 0.740 inches and 0.760 inches
Maximum Operating Temp:
125.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
1 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thread Size:
0.112 inches single group
Winding Operating Current:
75.0 milliamperes dc single component single secondary
Winding Power Rating:
5.7 volts-amperes single component single primary
Winding Operating Voltage:
60.00 dc volts single component single secondary
Test Data Document:
64547-805936 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5950-01-348-7902

Power Transformer - Page 2 of 2



Fiig:

A058b0