NSN 5950-01-349-9858

Current Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-349-9858

View Online at https://aerobasegroup.com/nsn/5950-01-349-9858
Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Moisture resistant and vibration resistant
Overall Length:
2.891 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.0625 inches single mounting facility single center group
Overall Height:
2.870 inches
Overall Width:
1.190 inches
Mounting Hole Diameter:
0.170 inches single group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Maximum Operating Temp:
85.0 degrees celsius
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 secondary single component
Winding Operating Current:
5.0 microamperes dc single component single primary
Winding Operating Voltage:
0.00 dc volts single component single secondary and 5.00 dc volts single component single secondary
Special Features:
Primary rated but not included
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-01-349-9858

Current Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0