

View Online at <https://aerobasegroup.com/nsn/5950-01-351-1927>

**Reliability Indicator:**

Not established

**Overall Length:**

0.800 inches

**Frequency Rating:**

20.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Overall Diameter:**

1.515 inches

**Maximum Operating Temp:**

125.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Features Provided:**

Tinned wire leads

**Winding Operating Current:**

0.1 amperes dc single component 1st secondary0.2 amperes dc single component 2nd secondary0.3 amperes dc single component 3rd secondary2.0 amperes dc single component 4th secondary6.0 amperes dc single component single primary

**Winding Operating Voltage:**

0.56 ac pounds per hour wet single component 1st secondary22.80 ac pounds per hour wet single component 2nd secondary8.44 ac pounds per hour wet single component 3rd secondary10.00 ac pounds per hour wet single component single primary

**Special Features:**

Terminal 8 is common to primary and 1st secondary winding; 1 primary and 5secondary windings

**Terminal Type And Quantity:**

11 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0