

View Online at <https://aerobasegroup.com/nsn/5950-01-351-1927>

Reliability Indicator:

Not established

Overall Length:

0.800 inches

Frequency Rating:

20.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Overall Diameter:

1.515 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Features Provided:

Tinned wire leads

Winding Operating Current:

0.1 amperes dc single component 1st secondary0.2 amperes dc single component 2nd secondary0.3 amperes dc single component 3rd secondary2.0 amperes dc single component 4th secondary6.0 amperes dc single component single primary

Winding Operating Voltage:

0.56 ac pounds per hour wet single component 1st secondary22.80 ac pounds per hour wet single component 2nd secondary8.44 ac pounds per hour wet single component 3rd secondary10.00 ac pounds per hour wet single component single primary

Special Features:

Terminal 8 is common to primary and 1st secondary winding; 1 primary and 5secondary windings

Terminal Type And Quantity:

11 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0